

IN-VT002F1 transmitter

IceSpy Dual channel 0-5v

Flexible and reliable multi-purpose analogue sensors within the Hanwell IceSpy series for monitoring multiple parameters such as CO2, air flow and differential pressure.

Features

- ✓ Superior performance hardware with high accuracy sensors
- ✓ Waterproof to IP65* (relates to Hanwell IceSpy transmitter, probes used with the transmitter may vary)
- ✓ All transmitters incorporate a wall bracket
- ✓ Easily accessible battery for user replacement, if required
- ✓ Low power radio for long distance transmission
- ✓ Up to 2 year battery life
- ✓ Complies with RoHS, EU directives and WEEE
- ✓ Carries CE Marking

Typical Applications

- Comprehensive measurement options for multiple applications across food, healthcare and pharmaceutical industries



Carbon Dioxide



Differential Pressure



Airflow



Compatible with Hanwell EMS

Product code: IN-VT002F1

Instrumentation specification									
Dimension (Excl. ancillaries)	165 x 65 x 35mm (40mm including mounting bracket)								
Weight	150g (including battery)								
Power supply	1 x 1.5V AA Lithium battery								
Case material	ABS								
Memory capacity	On board logging capability for 5 days								
Nominal logging interval	10 minutes								
IP rating	IP65								
Input type	2 Channels 0-5VDC								
Resolution	12 BIT								
Transmitter unit accuracy	+/- 0.18%								
System Accuracy - Airflow	<table border="1"> <thead> <tr> <th>Probe</th> <th>Accuracy</th> </tr> </thead> <tbody> <tr> <td>IN-AF05MS</td> <td>±0.2m/s +3% of measuring value</td> </tr> <tr> <td>IN-AF10MS</td> <td>±0.3m/s +4% of measuring value</td> </tr> <tr> <td>IN-AF20MS</td> <td>±0.4m/s +6% of measuring value</td> </tr> </tbody> </table>	Probe	Accuracy	IN-AF05MS	±0.2m/s +3% of measuring value	IN-AF10MS	±0.3m/s +4% of measuring value	IN-AF20MS	±0.4m/s +6% of measuring value
	Probe	Accuracy							
	IN-AF05MS	±0.2m/s +3% of measuring value							
IN-AF10MS	±0.3m/s +4% of measuring value								
IN-AF20MS	±0.4m/s +6% of measuring value								
Instrument operating range	-30°C to +50°C								
Storage temperature	-40°C to +85°C								

Radio transmitter functions	
Radio frequency	433-434MHz Band
Radio power	Max 10mW, duty cycle <0.1%
Radio range	300m over open ground
Nominal transmit interval	1 minute
Battery Life	Up to 2 years (dependent on use)
Software required	W900 – Standard EMS Software Package W906 – Validated EMS Software Package *See EMS datasheet for further options
Hardware required	IN-NR001F1 - Hanwell IceSpy Network Receiver IN-RP001F1 - Hanwell IceSpy Repeater (Repeater only required in special circumstances which would be discussed with you following your Signal Strength Test)
Probe specifications	Please refer to the Hanwell IceSpy Sensor datasheet
Accessories	
G301	AA 1.5V Lithium Battery
G301-4	AA 1.5V Lithium Battery pack of 4

Manufactured by Hanwell | Ellab

Version 4 - EC210035

Disclaimer: The information contained herein is believed to be reliable. Hanwell Solutions Ltd. is not responsible for any incorrect or incomplete information on this datasheet and the information or product may be changed without notice. Customers should obtain and verify the latest relevant information before placing orders for Hanwell products.

hanwell.com

Tel: +44 (0)1462 688070 | Email: sales.hanwell@ellab.com

Cable options (supplied separately)

Two cable options available

IN- LSC0.5	0.5 meter analogue transmitter connection cable
IN-LSC3.0	3 meter analogue transmitter connection cable

Analogue transmitter connection cable

