

TrackSense® Pro Basic Wireless Data Logger

Rigid and SmartFlex Temperature Sensor

Key Features & Benefits

- ✓ Unique [interchangeable sensor option](#)
- ✓ Real-time data option with [Sky module](#)
- ✓ Works in conjunction with the [ValSuite®](#) validation & calibration software
- ✓ FDA 21 CFR Part 11 compliant
- ✓ Temperature range of **-30 to +105 °C**
- ✓ Industry leading accuracy of **± 0.05 °C**
- ✓ Covers various applications within [pharmaceutical](#), [food](#) and [medical](#) industries



TrackSense® Pro Basic Data Loggers

The wireless [TrackSense® Pro Basic data loggers](#) are made of a high resistant stainless steel with cutting edge technology that allows for immensely accurate and stable measurements when performing various thermal processes.

All TrackSense® Pro data loggers are configured with [interchangeable sensors](#) able to measure temperature, vacuum, relative humidity, pressure, conductivity and CO₂.

Ellab's data loggers are easily activated and read by the [Multi reader station](#). When combined with the [Sky module](#), data loggers can provide real time data via wireless communication. Utilizing the numerous functions of the FDA 21 CFR, Part 11 compliant [ValSuite™ software](#), data is easily analyzed and distributed through various report options

Interested in this product? [Contact sales today](#)

Technical Specifications

Sensor with this logger configuration:	Rigid and SmartFlex Temperature Sensor
Temperature Measuring Range:	-30 to +105 °C
Measuring Principle:	Electrical Resistance
Sensor Element:	Pt1000
Diameter:	2 mm / 1.8 mm
Length:	From 100 mm - 1000 mm
Position of Measuring Point from Tip:	3 mm
Accuracy:	
-30 to -25 °C:	± 0.1 °C / ± 0.1 °C
-25 to -105 °C:	± 0.05 °C / ± 0.1 °C
Sensor Response Time:	
T-63%:	0.8 Second / 2.2 Seconds
T-90%:	1.7 Second / 4.3 Seconds
Logger with this sensor configuration:	Pro Basic 3G
Operating Temperature:	-30 to +105 °C
Operating Pressure:	0.001 mBar to 10 Bar ABS
House Material:	316L Stainless Steel
Diameter:	25 mm
Length:	44 mm
Weight with Battery:	48 Grams
Memory Capacity:	120,000 Data Points / 60,000 Samples
Minimum Sample Rate:	1 Second
Maximum Sample Rate:	24 Hours
Maximum Start Delay:	14 Days
Intrinsically Safe:	Ex II1GD Ex ia IIC T3 Ga, -30°C ≤ Tamb ≤ +105°C
Time Accuracy:	± 5 Seconds Per 24 Hours
Battery:	TSP Standard Battery

If equipment is used in ATEX environment, special [conditions for safe use are stated in ATEX certificates](#), section 17 must be considered.